SCHEDA TECNICA - *TECHNICAL SHEET*

CLAMPEX Fascetta metallica stringitubo
Metallic band clamp

DATI TECNICI - *TECHNICAL DATA*



dt	=	diametro tubo / *tube diameter*
Lr		larghezza banda / *band width*
t	=	spessore banda / *band thickness*
SW	=	chiave di manovra / *wrench*
Tinst	=	coppia di serraggio nominale / *torque*

dt [mm]	Lr [mm]	t W1 [mm]	t W2+ / W4 [mm]	SW [mm]	Tinst W1 [Nm]	Tinst W2+ / W4 [Nm]	Cod. W1	Cod. W2+	Cod. W4
8-12	9	0.7	0.7	7	3	4	38015b09012	38010009012	38000009012
10-16							38015b09016	38010009016	38000009016
12-20							38015b09020	38010009020	38000009020
12-22							38015b09022	38010009022	
16-25							38015b09025	38010009025	38000009025
16-27							38015b09027	38010009027	
20-32							38015b09032	38010009032	38000009032
25-40		0.8					38015b09040	38010009040	38000009040
30-45							38015b09045	38010009045	
32-50							38015b09050	38010009050	38000009050
40-60							38015b09060	38010009060	38000009060
50-70							38015b09070	38010009070	38000009070
60-80							38015b09080	38010009080	38000009080
70-90							38015b09090	38010009090	38000009090
80-100							38015b09100	38010009100	38000009100
90-110							38015b09110	38010009110	38000009110
100-120							38015b09120	38010009120	38000009120
16-27	12	0.7	0.7	7	5	7	38015b12027	38010012027	38000012027
20-32							38015b12032	38010012032	38000012032
25-35		0.8					38015b12035	38010012035	38000012035
25-40							38015b12040	38010012040	38000012040
30-45							38015b12045	38010012045	38000012045
32-50							38015b12050	38010012050	38000012050
40-60							38015b12060	38010012060	38000012060
50-70							38015b12070	38010012070	38000012070
60-80							38015b12080	38010012080	38000012080
70-90							38015b12090	38010012090	38000012090
80-100							38015b12100	38010012100	38000012100
90-110							38015b12110	38010012110	38000012110
100-120							38015b12120	38010012120	38000012120
110-130							38015b12130	38010012130	38000012130
110-140							38015b12140	38010012140	38000012140
130-150							38015b12150	38010012150	38000012150
140-160							38015b12160	38010012160	38000012160
150-170							38015b12170	38010012170	38000012170
160-180							38015b12180	38010012180	38000012180
170-190							38015b12190	38010012190	38000012190

Tinst=Tx0.7 (T = Torsione a rottura / *Break Torsion*)

CARATTERISTICHE PRODOTTO - *PRODUCT FEATURES*

Tipo / *Type*	W1	W2+	W4
Banda / *Band*	acciaio - zincatura bianca *steel - white zinc plated*	inox 203 EZ SAE *stainless steel 203 EZ SAE*	inox AISI 304 *stainless steel AISI 304*
Cassetto / *Housing*			
Vite / *Screw*		acciaio - zincatura bianca *steel - white zinc plated*	inox AISI 304 – zincatura bianca* *stainless steel AISI 304 – white zinc plated**

** trattamento superficiale con funzione antigrippante / Superficial treatment with anti-gripping function*

Fascetta metallica ***Metallic band***	Lr=9 mm			Lr=12 mm		
	W1	**W2+**	**W4**	**W1**	**W2+**	**W4**
TRAZIONE / *TENSILE* [1daN≅1Kgf]	*257*	*227*	*384*	*364*	*475*	*471*

I carichi riportati sono valori medi di rottura, derivano da prove eseguite presso il laboratorio Friulsider nel rispetto delle norme di riferimento. I valori di carico riportati hanno valore solo se l'installazione è stata eseguita correttamente. Il progettista è responsabile del dimensionamento, della scelta di un opportuno coefficiente di sicurezza ($\gamma \geq 2$) e del numero dei fissaggi. / *The load values are the mean ultimate loads which derive from tests carried out in the Friulsider laboratories in accordance with the appropriate standards. The load values are only valid if the installation has been carried out correctly. The design engineer is responsible for the designing, the choice of the appropriate safety factor ($\gamma \geq 2$) and for the number of fixings.*

FRIULSIDER
YOUR FIXING FACTORY